

IN THE CLAIMS:

Please cancel Claim 17 without prejudice or disclaimer of the subject matter presented therein.

Please add Claims 18-43:

C1
G14
Sub
D1

--18. (New) An optical scanning apparatus comprising:
a laser unit having a laser source and being configured to emit a
substantially parallel beam of light;
an incident optical system arranged to direct the light beam emerging from
the laser unit to strike an optical deflector while maintaining a width of the light beam
wider than a width of a deflecting surface of the optical deflector in a main scanning
direction; and
an imaging optical system for forming the light beam deflected by the
optical deflector into an image on a scanned surface,
wherein said laser unit is adapted to be shifted in a predetermined direction
with respect to an optical axis of said incident optical system.

19. (New) An optical scanning apparatus according to Claim 18,
wherein said laser unit is adapted to be shifted by a shift adjusting means in the
predetermined direction with respect to the optical axis of said incident optical system.

20. (New) An apparatus according to claim 18, wherein the illuminance distribution on the scanned surface falls within $\pm 5\%$ with respect to the scanning central axis in an effective scanning range.

21. (New) An apparatus according to claim 18, wherein the predetermined direction is the main scanning direction or/and a sub-scanning direction.

22. (New) An apparatus according to claim 18, wherein when the optical axes of said incident ²¹optical system and imaging ²²optical system are projected on a main scanning cross-section, the optical axes substantially coincide with each other.

23. (New) An apparatus according to claim 22, wherein the light beam emerging from said incident optical system is ^{less than 90°} obliquely incident on the deflecting surface of the optical deflector in a sub-scanning cross-section.

24. (New) An apparatus according to claim 18, wherein the light beam emerging from said incident ²¹optical system is obliquely incident on the deflecting surface of the optical deflector in a main scanning cross-section. Fig. 1

25. (New) An apparatus according to claim 24, wherein said incident ²¹optical system is arranged in a main scanning cross-section based on the optical deflector. ¹⁰

26. (New) An apparatus according to claim 18, wherein said incident optical system comprises a stop plate, and said laser unit is shifted in the predetermined direction with respect to the optical axis of said incident optical system such that a ratio of intensities of two light beams obtained by splitting a light beam passing through said stop plate in two in the main scanning direction at a stop center becomes not more than 10%.

27. (New) An apparatus according to claim 18, wherein a tilt angle of the light source in the main scanning direction is set to not more than $\pm 2.5^\circ$ with respect to the optical axis of the laser unit.

28. (New) An apparatus according to claim 24, wherein said laser unit is shifted in advance in the main scanning direction with respect to the optical axis of said incident optical system by an amount corresponding to an incidence angle at which the light beam emerging from said incident optical system is obliquely incident on the deflecting surface of the optical deflector in a main scanning cross-section.

29. (New) An image forming apparatus comprising:
said optical scanning apparatus defined in any one of claims 18 to 28;
a photosensitive member placed on the scanned surface;

a developing unit for developing an electrostatic latent image formed on said photosensitive member by a light beam scanned by said optical scanning apparatus into a toner image;

a transfer unit for transferring the developed toner image onto a transfer medium; and

a fixing unit for fixing the transferred toner image on the transfer medium.

30. (New) An image forming apparatus comprising:

said optical scanning apparatus defined in any one of claims 18 to 28; and

a controller for converting code data input from an external device into an image signal, and inputting the signal to said optical scanning apparatus.

31. (New) A method for performing optical scanning using an optical

scanning apparatus including a laser unit having a laser source and being configured to emit a substantially parallel beam of light, an incident optical system arranged to direct the light beam emerging from the laser unit to strike an optical deflector while maintaining a width of the light beam wider than a width of a deflecting surface of the optical deflector in a main scanning direction, and an imaging optical system for forming the light beam deflected by the optical deflector into an image on a scanned surface, the method comprising the step of:

shifting the laser unit in a predetermined direction with respect to an optical axis of the incident optical system.

32. (New) The method according to Claim 31, wherein the laser unit is shifted by a shift adjusting means in the predetermined direction with respect to the optical axis of the incident optical system.

33. (New) The method according to claim 31, wherein the illuminance distribution on the scanned surface falls within $\pm 5\%$ with respect to the scanning central axis in an effective scanning range.

34. (New) The method according to claim 31, wherein the predetermined direction is the main scanning direction or/and a sub-scanning direction.

35. (New) The method according to claim 31, wherein when the optical axes of the incident optical system and imaging optical system are projected on a main scanning cross-section, the optical axes substantially coincide with each other.

36. (New) The method according to claim 35, wherein the light beam emerging from the incident optical system is obliquely incident on the deflecting surface of the optical deflector in a sub-scanning cross-section.

37. (New) The method according to claim 31, wherein the light beam emerging from the incident optical system is obliquely incident on the deflecting surface of the optical deflector in a main scanning cross-section.

38. (New) The method according to claim 37, wherein the incident²¹ optical system is arranged in a main scanning cross-section based on the optical¹⁰ deflector.

39. (New) The method according to claim 31, wherein the incident optical system comprises a stop plate, and the laser unit is shifted in the predetermined direction with respect to the optical axis of the incident optical system such that a ratio of intensities of two light beams obtained by splitting a light beam passing through the stop plate in two in the main scanning direction at a stop center becomes not more than 10%.

C1
Cont
D Sub
by
40. (New) The method according to claim 31, wherein a tilt angle of the ^{laser} light source in the main scanning direction is set to not more than $\pm 2.5^\circ$ with respect to the optical axis of the laser unit.

41. (New) The method according to claim 37, wherein the laser unit is shifted in advance in the main scanning direction with respect to the optical axis of the incident optical system by an amount corresponding to an incidence angle at which the light beam emerging from the incident optical system is obliquely incident on the deflecting surface of the optical deflector in a main scanning cross-section.

42. (New) An image forming method comprising the steps of: